

# TECHNICAL DATA SHEET

## OAK INNSBRUCK 190 CHARACTER



This image is a representation of the flooring and may not be identical to the actual floor. Light, camera, printing all affect the colour and look of the floor.

### Product Details

|                      |                                            |
|----------------------|--------------------------------------------|
| Code                 | 7016-2813                                  |
| Length               | 1900mm                                     |
| Width                | 190mm                                      |
| Thickness            | 15mm                                       |
| Wear Layer           | 3mm Oak (Quercus Robur)                    |
| Colour               | Invisible effect                           |
| Finish               | Brushed & Matt Lacquered                   |
| Join                 | Click - 4V                                 |
| Grade                | Character                                  |
| Middle Later approx  | 9mm poplar (Populus Simonii)               |
| Counterpart approx   | 2mm poplar (Populus Simonii)               |
| Rel. humidity        | 7% ± 2%                                    |
| Weight per unit area | Approx/ 8.15 kg/m                          |
| Pallet               | 40 Packages 115.52 m2                      |
| Pack Size            | 6 Pieces 2.888 m2 (max. 16% short Lengths) |

### Technical Information

|                               |             |
|-------------------------------|-------------|
| Durability class              | 1           |
| Slip Resistance               | NPD         |
| Fire behaviour                | Dflsl       |
| Emission of formaldehyde      | E1          |
| Emission of pentachlorophenol | ≤ 5 ppm     |
| Thermal conductivity          | 0.13 W/(mK) |
| Breaking strength             | NPD         |

### Notes:

All Floors4ever floors must be fitted by fully insured, skilled professionals who understand the unique requirements of each installation. Our warranty exclusively covers floors installed by competent flooring specialists meeting British or international professional standards. We strongly recommend consulting our Installation Guides and Warranty Policy for comprehensive guidance.

Wood is a naturally variable product, which means each floor is plank is unique. No sample or image can perfectly capture the complete character of a finished floor. When exposed to light, wood undergoes subtle colour transformations; darker wood species typically develop a warm, golden tone, while lighter woods gradually become slightly darker. During the production process, cracked knots are filled with putty, and it's normal to occasionally observe small gaps between the putty and the wood.

At the time of writing and publication of this sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in the sheet are intended only as illustrations. No rights can be derived from them.

Address: Olympic Warehouse, 100 Colindeep Lane  
London NW9 6HB  
Tel: +44 20 3915 3792  
Email: [info@floors4ever.co.uk](mailto:info@floors4ever.co.uk)  
Website: [www.floors4ever.co.uk](http://www.floors4ever.co.uk)